



NOTES:

1. INTAKE AND DISCHARGE PIPING CONNECTIONS & SEAL FLUSH LINE MUST BE FIELD INSTALLED & ADEQUATELY SUPPORTED TO PREVENT INDUCED PIPING LOADS ON TO THE PUMP SYSTEM.
2. DIMENSIONS SHOWN ARE INCHES ±.25". DIMENSIONS IN PARENTHESES () ARE FOR REFERENCE ONLY.
3. TOTAL SKID WEIGHT WITH MOTOR & PUMP=21,623 LBS APPROX. MOTOR WEIGHT=8350 LBS, APPROX. TOTAL PUMP WEIGHT=2745 LBS, APPROX.
4. INTAKE SHOWN IN AS-BUILT ORIENTATION. INTAKE CAN BE ORIENTED IN MULTIPLE DIRECTIONS. INTAKE FLANGE BOLT HOLES EQUALLY SPACED TO STRADDLE VERTICAL INTAKE CENTERLINE.
5. REFER TO EDA-3890 FOR FOUNDATION DETAILS.
6. REFERENCE DRAWING 307082 FOR HTC OIL COOLER CONNECTION LAYOUT.
7. TANDEM (MULTIPLE) SKIDS SHOULD NEVER BE LIFTED, TRANSPORTED OR OTHERWISE MOVED WHILE FASTENED TOGETHER. ALWAYS REMOVE INTERCONNECTING BOLTING BETWEEN SKIDS PRIOR TO MOVING ASSEMBLIES TO PREVENT DAMAGE TO EQUIPMENT.

